# **3M<sup>TM</sup> PBPO/C 6-12** Indoor Distribution Box "Floor Box"



Distribution Box PBPO/C 6-12 4 trays 1 Slot 6 Fibrlok 2540G 12 drops SC coupling

# Features

- Sliding cover
- Cable entries
  - 2 anchoring points for riser cable
- 4 slots organiser BPEO Evolution style
- Mechanical or fusion splices
- Capability for splitters
- Large storage area for cable modules or bare fibres
- Re-enterable for the addition of further cables

Inddor distribution box suitable for connecting between vertical distribution and equipment.

Datasheet

Can be as "end-distribution box" and "window-cut distribution box"

Composition :

- 1 vertical area with two strain reliefs for riser cable
- 1 storage area for cable modules and fibres
- 1 4 slot organiser BPEO Evolution type
- 1 to 4 trays for splices or splitters
- Trays for fusion, mechanical splicing and splitters
- Capacity from 12 to 48 splices
- 1 connector panel for 12 SC type couplings

A PBPO version is also available for drop cables.

## **Benefits**

- Adapted to building riser
- Installation for window-cut riser distribution applications
- Fibre management without overtubing
- Combination of many types of trays
- The trays, couplings and pigtails are available as separate parts

# **Specification**

General product features		Specification			
<ul> <li>Distribution cable : maximum diameter 13,5 mm Strain relief with 2 ties</li> <li>4 slot organiser, trays 5 &amp; 10 mm <i>BPEO Evolution</i> range</li> <li>Outlet : 12 pigtails SC/PC or APC in 250 µm or 900 µm and 12 couplings simplex SC/PC or APC</li> <li>The trays, couplings and pigtails are available as accessories</li> </ul>		Degree of protec- tion (EN 60 529)	- IP 30 / IK08		
		Installation:	Screws (2 x M4) ( not supplied )		
Capacity <ul> <li>Fusion Splices</li> <li>24</li> <li>6 or 12 per tray</li> </ul>		Dimensions ( in mm )	without fixing supports		
Mechanical Splice*	24 6 or 12 per tray	Support	Length	Width	Depth
• Splitter 1 by 8	2 1 splitter and 9 fusion splices per 10 mm tray		204	158	52
	( "2PAS")	Colour	White		
* Fibrlok 2540G		Material	Thermoplastic		
Ordering informatio	n	Ref. No			
PBPO/C Internal distrib 4 slot organiser Connector plate for 12 Trays for Splices	ution box 2 SC/PC or SC/APC couplings	N5	01506A	50150	6
• BPEO-K7-1SLOT -12 Tray 1 slot depth suitable f	N5	41106A	54110	5	

Tray equipped with cover	
• <b>BPEO-K7-1 SLOT -6 Fibrlok2540G</b> Tray 1 slot depth suitable for 6 mechanical splices Fibrlok 2540G Tray equipped with cover	
· PPEO-KZ-2 SLOT -12 Sibrick2540G	

#### BPEO-K7-2 SLOT -12 Fibrlok2540G N541108A 541108 Tray 2 slot depth suitable for 12 mechanical splices Fibrlok 2540G Tray equipped with cover **Trays for Splices & Splitters BPEO-K7-1 SLOT -9 fusion & PLC splitter** In Qualification Tray 1 slot depth suitable for 9 fusion splices 45 or 60 mm long Splitter space: 4x4x6 mm . Tray equipped with cover **BPEO-K7-2 SLOT -12 fusion & splitter** Tray 2 slot depth suitable for 12 fusion splices 45 or 60 mm long N541104A 541104 Splitter space: 70x10x6 mm Tray equipped with cover

# BPEO-K7-2 SLOT -10 Fibrlok 2540G & splitter

Tray 2 slot depth suitable for 10 mechanical splices Splitter space: 70x10x6 mm. Tray equipped with cover

### 3M is a trademark of 3M.

Important Notice

Buyer and/or user of this 3M product has to make sure before using this product that it is suitable for the intended use. All questions of liability relating to this product are subject – in accordance with the prevailing law – to the Terms of Sale of the selling 3M subsidiary.

 $3\ensuremath{\mathsf{M}}$  is trademark of the 3M company. SID is a trademark of the Quante AG.

N541103A

N541110A

541103

541110

# **3**M

3M Telecommunications		
Europe, Middle East & North Africa	Tel:	++49 (0)2131 / 14-5999
3M Deutschland GmbH	Fax:	++49 (0)2131 / 14-5998
Carl-Schurz-Strasse 1 . 41453 Neuss . Germany	Internet: w	ww.3MTelecommunications.com

Dr.Nr. 07-401-00500/07.2007 KL Index 0 Rights reserved to make technical alterations.